

433/S - 433/L

Surface-mounted louvres Pressure-relief damper

SURFACE-
MOUNTED
LOUVRE

ALUMINIUM



MATERIAL

- Made from aluminium sections: AlMgSi 0.5 [according to EN 12020-2]
- Finishing: anodized in satin colour [20 micron] or powder-coated in any RAL or Syntha Pulvin colour [40 micron]
- Extractor hood louvres: the blades open at the same time
- Pressure-relief louvres: the blades open individually
- Standard: without insect screen
- Opening pressure: 10 Pa standard, 20 Pa with enhanced blade

DIMENSIONS PRESSURE-RELIEF DAMPER 433/L

- Height: [multiple of 100] + 328 mm
- Minimum dimensions: 300 x 328 mm
- Thickness: 29 mm
- In length, the blades are in one piece up to 800 mm

DIMENSIONS EXTRACTOR HOOD LOUVRE 433/S

- See stock models

FIXING

- Invisible fixing
- Screws and plugs are included

OPTIONS

- Stainless steel 304 mesh [6x6/10x10/20x20 mm] or without
- Insect screen or mesh in stainless steel 316

TYPICAL APPLICATIONS


- Extractor hood
- Drying cabinet

STOCK MODELS

Dimensions (W x H) mm	Natural colour anodised	Renson Standard WHITE	RAL 8019	STR 7016	STR 9005
Extractor hood louvres 433/S					
173 x 173	04331731	04331736		04331733	04331739
210 x 210	04332101	04332106		04332103	04332109
246 x 246	04332461	04332466	04332467		
Pressure-relief dampers 433/L					
328 x 328	00433328				
428 x 428	00433428				
528 x 528	00433528				

TECHNICAL DRAWINGS

Renson® Technology extractor hood louvre 433/S



Pressure-relief damper 433/L

